

Quilted Pants









Materials Requirements

Denim Jeans

Focus Fabric

• 1 yard

Hem Fabric

• 1/2 yard

Backing

• 1 yard

Batting

• 1 yard

General Notes

- WOF = Width of Fabric
- All seams are sewn with a ½ inch unless specified

Cut Your Fabric

Focus Fabric

• Triangle piece 2" at the top and between 3"- 6" at the bottom

Hem Fabric

• Two Inch Strips

Piece Your Pants

- 1 Use your seam ripper to open the side seams along the legs
- 2 Undo the bottom hem
- 3 Measure the bell bottom fabric 2" at the top and the bottom needs to measure between a 3" - 6" taper
- **4** Measure the height of your open seam and add 2"
- **5** You can patch it together or cut out of one fabric
- 6 Cut two panels for the front and back for each leg
- 7 Quilt as desired
- 8 Turn your pants inside out
- 9 Lay the triangular panel face down on the open seam
- **10** Make ure the fabric is 2" about the open seam at the thigh or knee
- **11** Straight stitch from the top of the triangle to the bottom hem
- **12** When you sew on the other side of the panel cross over the first stitch

- **13** Finish the raw edges on each seam with a zig zag stitch
- 14 Repeat on the other leg
- 15 Cut a hem from your focus fabric
- 16 Iron in half
- 17 Sew hem on with a straight stitch
- 18 Fold and Iron fabric up to the hem
- 19 Stitch the other side